

TDS: (Technical Data Sheet)



Global Universal Hydraulic Oil Series; GHOS-10100

Global Hydraulic Oils are specially formulated to provide superior lubrication in food plant machinery. These semi synthetic oils provide outstanding anti-wear protection, are compounded to prevent rusting in the presence of moisture, are non-foaming and have rapid water separation characteristics. An effective antioxidant gives long oil service life and reduces the possibility of sludge and varnish formation. These oils provide anti-wear protection that meets all the requirements of major hydraulic pump manufacturers such as Cincinnati Milicron P-68, P-69, P- 70 and Vicker's 104.

Special Features & Benefits:

- Resistance to oxidative breakdown even at high temperatures
- Long-term protection from rust and corrosion
- Keeps systems free of sludge and varnish
- Prevents pump, actuator and circulating system damage in moist or wet operations
- Ensures smooth & reliable operation of hydraulic valves & actuators
- Results in longer fluid life and reduced downtime in tough operating environments
- Resistance to contamination
- Rapidly separates from water without loss of performance additives
- Anti-wear protection & protects metal pump parts from scuffing & scoring
- Protects equipment operating for extended periods in tough Conditions
- Highly resistant to foaming and air entrapment
- Extends equipment life and improves operating reliability
- Prevents reservoir over flow

Technical Characteristics:

	Typical Analysis						
ISO GRADE	10	15	22	32	46	68	100
Viscosity @ 40°C, cst	11.0	15.0	21.5	32.5	46.5	68.5	98.3
Viscosity @ 100°G, cst			4.20	5.58	6.76	8.85	11.18
Viscosity @ 100°F, SUS	65	83	113	169	240	354	542
Viscosity @ 210°F, SUS			40.4	45.0	48.9	56.1	64.6
Viscosity Index	95	95	96	98	98	98	98
Pour Point, °F/°C	-10/-22	+10/-22	0/-18	0/-18	0/-18	0/-18	5/-15
Flash Point, °F/°C	365/185	370/187	395/202	420/216	440/226	465/240	475/246
API Gravity	33.2	33.2	33.0	32.2	32.0	31.7	30.9
Color	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Acid Number, mg KOH/g	0.15	0.15	0.15	0.15	0.15	0.15	0.15
Distilled Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Synthetic Sea Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Minutes to 3 mLaa	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Hours to 2.0 Acid #	6000+	6000+	6000+	6000+	6000+	6000+	6000+

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.